				Material S	afety Data She
(C)	MSD	SR	epo		
Applicant's name	Shenzhen Hu	ugnen Technolo	ogy (HGT) Co .,	LTD	
Applicant's Address	B2, Baolihua	Industrial Park	, Baihua Comm	unity, Guangm	ing Shenzhen
Name of Sample	Polymer Li-io	n Battery	(.c [*])		(\mathcal{C}^{*})
Model	631646				
Nominal Voltage	3.7V	(C)		(C)	
Rated Capacity	400mAh, 1.48	8Wh			
Weight	8.5g		Ø		S
Size (L×W×T)	(48.5×16.0×6	5.3)mm			
Prepared By	1B/F., Buildin	-	nology Co., Lto dustrial Park, C ong, China.		j, Baoan
Report No.	TCT190725H	1008			
Written by:	ny Wang	Appro	oved by:	Allen 8	ìn
2	4 7:			•	LISTING TECHNO
nspected by:	y long		Date: _	2019. 0	

l n

Material Safety Data Sheet

Material Safety Data Sheet Section 1- Chemical Product & Company Identification Name of Sample Polymer Li-ion Battery Manufacturer's Shenzhen Hugnen Technology (HGT) Co., LTD name Manufacturer's B2, Baolihua Industrial Park, Baihua Community, Guangming Shenzhen Address Contact Person Mr. Sun Tel +86-755-23420683 Fax +86-755-23420686 Emergency Tel +86-755-23420683 E-mail sun@hugnen.com Section 2- Hazards Identification

Classification of Danger	See section 14.		
Primary Route(s) of Exposure	Eye, skin contact, ingestion.		
Health Hazard		onditions. In case of ab components, which cou following cases: charg	use, there's Hazard of rupture, Id cause casualty loss. Abuses ged for long time, short
Report No.: TCT190725F Hotline: 400-6611-14		Fax: 86-755-27673332	Page 2 of 8 http://www.tct-lab.com

Chemical Name	Concentration or concentration ranges (%)	CAS Number
Lithium Cobalt Oxide	15-40	12190-79-3
Graphite	10-30	7782-42-5
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3
Copper	7-13	7440-50-8
Aluminum foil	5-10	7429-90-5
Nickel	1-5	7440-02-0

Labeling according to EC directives.

No symbol and Hazard phrase are required.

TCT通测检测 TESTING CENTRE TECHNOLOGY

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures

Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5- Fire Fighting Measures Characteristics of Dusts at sufficient concentrations can form explosive mixtures with air. Combustion Hazard generates toxic fumes. Hazardous Combustion Carbon dioxide. **Products** Fire-extinguishing Methods and For small fires, use water spray, dry chemical, carbon dioxide or chemical foam. Extinguishing Media Report No.: TCT190725H008 Page 3 of 8

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

	Material Safety Data Sheet
Attention inWear self-contained breathFire-extinguishing(approved or equivalent) a	hing apparatus in pressure-demand, MSHA/NIOSH nd full protective gear.
Section 6- Accidental Release Measu	ıres
Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.
Section 7- Handling and Storage	
	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.
Handling	disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect
Section 7- Handling and Storage Handling Storage Other Precautions	disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out
Handling Storage	 disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children. In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.
Handling Storage Other Precautions	 disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children. In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

				Eye and Face Protection: None	e required for
				consumer use. If there is a Haz sealing safety goggles. Face p	zard of contact: Tight
Personal	Protectiv	e Equipment		Skin and Body Protection: Non consumer use. If there is a Haz	e required for zard of contact: Wear
				protective gloves and protective Respiratory Protection: No protection	
				needed under normal use cond limits are exceeded or irritation ventilation and evacuation may	ditions. If exposure is experienced,
			6		
Section	9- Phys	ical and Chemic	al Prop	perties	
	,	Appearance: Prisma			
Physical S	State	Color: Silver		(\vec{c})	(\vec{c})
		Odour: If leaking, sm	ells of me	edical ether.	
Change ir	n conditic	on			/
pН		Not applicable as supplied.			
Flash Point		Not applicable unless individual components exposed.			
Flammabilit	,	Not applicable unless individual components exposed.			
Relative der	nsity:	Not applicable unless	s individua	al components exposed.	
Solubility (w	ater)	Not applicable unless individual components exposed.			
Solubility (o	ther)	Not applicable unless individual components exposed.			
Section	10 – Sta	ability and React	ivity		
Chemical	Stability			Stable under recommended sto	rage conditions.
Possibility	of Haza	rdous Reactions		None under normal processing.	
Condition	s to Avoi	d		Exposure to air or moisture over	r prolonged periods.
Incompati	ble mate	rials		Acids, Oxidizing agents, Bases.	
Hazardou	s Decor	position Products		Carbon oxides.	

Material Safety Data Sheet

Irritation		In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.		
Sensitization		Not Available.		
Reproductive Toxicity		Not Available.		
Toxicologically Synergistic M	aterials	Not Available.		
) (23)				
Section 12-Ecological Inf	ormation			
General note:		Do not allow undiluted product or large quantities of to reach ground water, water course or sewage system.		
Anticipated behavior of a che in environment/possible envir impact/ ecotoxicity		Not Available.		
Section 13 – Disposal Co	nsiderations			
Waste Treatment		Recycle or dispose of in accordance with		
	t	government, state & local regulations. Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is		
	t	government, state & local regulations. Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high		
Attention for Waste Treatmen		government, state & local regulations. Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is		
Attention for Waste Treatmen Section 14 – Transport In		government, state & local regulations. Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is		
Waste Treatment Attention for Waste Treatmen Section 14 – Transport In UN number Proper shipping name	formation 3480 & 3481 Lithium ion batter Lithium ion batter polymer batteries	government, state & local regulations. Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.		
Attention for Waste Treatmen Section 14 – Transport In UN number	formation 3480 & 3481 Lithium ion batter Lithium ion batter polymer batteries Lithium ion batter	government, state & local regulations. Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.		

Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section II, PI 966 Section II and PI 967 Section II appropriate of IATA DGR 60th (2019 Edition) for transportation.
IMDG CODE:	The batteries are not restricted to IMDG Code 2018 Edition (Amdt 39-18) according to special provision 188.
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2019.

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

Section 15 – Regulatory Information

Dangerous Goods Regulations

Recommendations on the Transport of Dangerous Goods-Model Regulations (20th revised edition)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG Code 2018 Edition Amdt 39-18)

Technical Instructions for the Safe Transport of Dangerous Goods

Classification and code of dangerous goods (GB 6944-2012)

2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws




Material Safety Data Sheet

Section 16 – Additional Information

MSDS creation date: 2019 Version: 2.0

Sample photo:



To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report*****

Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China Report Search Number: TCT190725H008 Search System: http://www.tct-lab.com Page 8 of 8